

IAPMO OCEANIA

7-11 Fullard Road, Narre Warren, Victoria 3805, Australia /info@iapmooceania.org



CERTIFICATE OF CONFORMITY

IAPMO Oceania hereby grants to:

Vola A/S

A.B.N.:

Lunavej 2, Horsens DK-8700 Denmark

Email: ch@vola.dk

the right to use the WaterMark in accordance with the ABCB Manual for the WaterMark Certification Scheme;– Australian Standards; WaterMark Technical Specifications; and the Plumbing Code of Australia; only in respect of the certified product as described in the WaterMark Certificate of Conformity – Schedule of Certified Product (Refer also IAPMO Product Listing Directory). The Certificate is granted subject to the rules governing the WaterMark Certification Scheme and the Terms and Conditions of the Approved User Agreement and IAPMO Oceania's WaterMark Governance Rules.

Evaluated to:

AS 4032.4-2014

Water supply - Valves for the control of heated water supply temperatures - Thermostatically controlled taps for the control of heated water supply temperatures

Manufacturer:

Refer to Licence Holder

Licence No.: WM-032123

First Certified: 02 Dec 2021

Certification Date: 13 Mar 2026

Expiry Date: 01 Dec 2026

David Viola

Chief Executive Officer of the IAPMO Group

This WaterMark certification is for the period indicated herein and is void after the date shown above. Any change in material, manufacturing process, marking or design without having first obtained the approval of IAPMO Oceania, or any evidence of non-compliance with applicable Standards, Specifications or of inferior workmanship, may be deemed sufficient cause for revocation of this certification. Reproduction of or reference to this certificate for advertising purposes may be made only by specific written permission of IAPMO Oceania. This certificate can only be reproduced in its entirety. Any alteration of this certificate could be grounds for revocation of this certification.

"This certificate is issued by a JAS-ANZ accredited Conformity Assessment Body. The ABCB and JAS-ANZ do not in any way warrant, guarantee or represent that the product the subject of this Certificate conforms to the WaterMark Certification Scheme Rules, nor accepts any liability arising out of the use of the product. The ABCB disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate."



WATERMARK CERTIFICATE OF CONFORMITY

SCHEDULE OF CERTIFIED PRODUCT



Certificate Holder
Vola A/S

A.B.N.:
Lunavej 2, Horsens DK-8700 Denmark

Manufacturer
Refer to Licence Holder

Standard
AS 4032.4-2014

Water supply - Valves for the control of heated water supply temperatures -
Thermostatically controlled taps for the control of heated water supply
temperatures

Licence No. WM-032123

Certification Date: 13 Mar 2026

Expiry Date: 01 Dec 2026

First Certified: 02 Dec 2021

Brand Name	Model Name	Model ID	Product Type	Product Description	Application	Nominal Size	End Connection	Nominated pre-set Temperature	Limitation of Temperature Adjustment	Material	Lead Free Compliant
VOLA	VOLA	5400FV	Thermostatic Mixing Valve	Thermostatic mixer with diverter and two outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400FVA3	Thermostatic Mixing Valve	Thermostatic mixer with diverter and three outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400FVA4	Thermostatic Mixing Valve	Thermostatic mixer with diverter and four outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400NV	Thermostatic Mixing Valve	Thermostatic mixer with diverter and two outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400NVA3	Thermostatic Mixing Valve	Thermostatic mixer with diverter and three outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400NVA4	Thermostatic Mixing Valve	Thermostatic mixer with diverter and four outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400RV	Thermostatic Mixing Valve	Thermostatic mixer with diverter and two outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400RVA3	Thermostatic Mixing Valve	Thermostatic mixer with diverter and three outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400RVA4	Thermostatic Mixing Valve	Thermostatic mixer with diverter and four outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400RVX	Thermostatic Mixing Valve	Thermostatic mixer with diverter and two outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400RVXA3	Thermostatic Mixing Valve	Thermostatic mixer with diverter and three outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400RVXA4	Thermostatic Mixing Valve	Thermostatic mixer with diverter and four outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400TV	Thermostatic Mixing Valve	Thermostatic mixer with diverter and two outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A

Brand Name	Model Name	Model ID	Product Type	Product Description	Application	Nominal Size	End Connection	Nominated pre-set Temperature	Limitation of Temperature Adjustment	Material	Lead Free Compliant
VOLA	VOLA	5400TVA3	Thermostatic Mixing Valve	Thermostatic mixer with diverter and three outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400TVA4	Thermostatic Mixing Valve	Thermostatic mixer with diverter and four outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400TVX	Thermostatic Mixing Valve	Thermostatic mixer with diverter and two outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400TVXA3	Thermostatic Mixing Valve	Thermostatic mixer with diverter and three outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400TVXA4	Thermostatic Mixing Valve	Thermostatic mixer with diverter and four outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400V	Thermostatic Mixing Valve	Thermostatic mixer with diverter and two outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400VA3	Thermostatic Mixing Valve	Thermostatic mixer with diverter and three outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400VA4	Thermostatic Mixing Valve	Thermostatic mixer with diverter and four outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5600V	Thermostatic Mixing Valve	Thermostatic mixer with diverter and two outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5600VA3	Thermostatic Mixing Valve	Thermostatic mixer with diverter and three outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5600VA4	Thermostatic Mixing Valve	Thermostatic mixer with diverter and four outlets	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5100	Thermostatic Mixing Valve	Thermostatic mixer	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5100X	Thermostatic Mixing Valve	Thermostatic mixer	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5200V	Thermostatic Mixing Valve	Thermostatic mixer	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5300	Thermostatic Mixing Valve	Thermostatic mixer	Shower/Bath	G3/4	G3/4	38°C	45°C	DR Brass	N/A
VOLA	VOLA	5400DV	Valve and Tap Accessories	Diverter and 4 outlets for use with a thermostatic mixer	Shower/Bath	G3/4	G3/4	N/A	N/A	DR Brass	N/A
VOLA	VOLA	5400DVA3	Valve and Tap Accessories	Diverter and 4 outlets for use with a thermostatic mixer	Shower/Bath	G3/4	G3/4	N/A	N/A	DR Brass	N/A
VOLA	VOLA	5400DVA4	Valve and Tap Accessories	Diverter and 4 outlets for use with a thermostatic mixer	Shower/Bath	G3/4	G3/4	N/A	N/A	DR Brass	N/A

END RECORD

END RECORD



David Viola
Chief Executive Officer of the IAPMO Group